HOOKER BOATS CABIN MODELS FEATURES 2025

• Standard O Optional ‡ Not available

Г	leense.	67550	locc l
	650SC	675SC	8SC
Hardware			
Bow roller stainless	•	•	•
U-bolts and tow eyes stainless	•	•	•
Bollard stainless	•	•	•
Stainless steel fold up cleats	•	•	•
Standard horn cleats	‡	‡	‡
Stainless rod holders standard	•	•	•
Hand rails ss in combings	•	‡	‡
Storage/ esky			
Shelves in cabin	•	•	•
Storage under bunks	•	•	•
Anchor well single	•	•	•
Anchor well double hatch	‡	‡	•
Under floor kill pen	•	•	•
Tackle draw	0	0	0
Dash rear access panel	•	•	•
Electrical			
Switch panels	•	•	•
Single bilge and float switch	•	‡	‡
Dual bilge and float switch	О	•	•
LED navigation lights	•	•	•
Battery tray x1	•	•	•
Master switch for batteries	•	•	•
Floodlight	0	0	0
Steering			
Hydraulic steering	•	•	•
Plumbing			
Fresh water tank	0	•	•
Live bait tank plumbed	0	0	0
Deck wash plumbed	•	•	•
Canopies			
Fibreglass hardtop	0	0	0
Extension to hardtop - painted alloy	0	0	0
Alloy canopy powdercoated	0	0	0
Stainless Steel and Aluminium			
Boarding ladder	•	•	•
Aluminium painted bow rail	0	•	•
Bait board	0	•	•
Fuel			
Fuel sender unit	•	•	•
Seating			
Removable rear seats	•	•	•
Bucket pedestals	•	•	•
Space frame seating	•	•	•
Insulated seat bases	0	0	0
mounated seat pases	<u></u>	<u> ~ </u>	\sim

Fiberglass components			
recess for fire ext and epirb	0	•	•
Electric bow mount	0	0	0
Side Pockets	•	•	•
Side pockets with LED light	•	•	•
Feet recess - side pockets	•	•	•
Console access door	‡	‡	‡
Transom door	•	•	•
Bow sprite	•	•	•
Footrest	•	•	•
Windscreens/ hatches			
Polycarb windscreen/ or wavebreaker	•	‡	‡
Toughened glass windsccreen	0	•	•
Structural			
Biaxial 887 wovings	•	•	•
316 Stainless fasteners	•	•	•
Foam Filled closed cell	•	•	•
No timber	•	•	•
10Yr structural hull warranty (1 Year commercial)	•	•	•
Specifications			
Length over all (mtrs)	6.6	6.75	7.8
Length on trailer (mtrs)	7	8	9
Beam (mtrs)	2.15	2.4	2.4
Draft (mm)	300	300	400
Weight (Hull dry weight) KG	1000	1200	1350
Deadrise (degrees)	19	22	24
Fuel (litres)	300	380	500
HP rating single engine	225	250	300
HP rating twin engines	230	250	300
Max motor weight (kg) single engine	295	295	395
Max. motor weight (kg) twin engines	590	590	790
Max KW single engine	168	186	224
Max People weight (kg)	450	540	720
Max carry weight (kg)	1000	1300	1500
Freeboard - (mm)	720	700	700
Height on trailer (mtrs)	2.35	3	3.1
Foam Filled buoyancy	STD	STD	STD

weights are approx and can vary. Note: Features list as of Oct 1, 2023 orders.

 $Whilst\ every\ care\ has\ been\ taken\ to\ provide\ accurate\ information,\ weights\ and\ specs\ can\ differ\ due\ to\ being\ hand\ made\ boats.$

Motor weights include rigging, battery and accessories